
CHARRED MOUNTAIN BIRCH LOG PLACEMENT INSTRUCTIONS

CAUTION......WARNING.....IMPORTANT





CHMBW-24 shown



If this log set is to be setup on a G31 burner, disregard this instruction and follow the G31 supplemental instruction supplied with the G31 burner system.

LOG SET IMPORTANT INFORMATION

This instruction contains recommended log placement for these Real Fyre logs which will promote good combustion and provide superior flame pattern and appearance. **Use these logs only with a Peterson burner system**.

Adequate ventilation is absolutely necessary! Provided significant, noticeable sooting does not occur, some flexibility is possible in log placement to suit your individual preference (see Important below). If you experience a continued accumulation of black carbon (soot) on your logs it is an indication of incomplete combustion and you should move the effected log(s) so as to minimize the flame contact on the effected log(s). If significant sooting continues, stop using this gas log set.

Please read these instructions completely and carefully.

Important: Adequate ventilation is absolutely necessary. Adequate spacing between the logs is NECESSARY and MUST be maintained. Some carbon build up (sooting) may occur where flames strike the logs. If carbon build up (sooting) continues, rearrange top logs to allow more opening(s) for flame(s) before sooting becomes worse. If any sooting occurs outside of the firebox (i.e. on the walls), turn off unit immediately and contact a qualified professional service technician. WARNING: Use ONLY Peterson Real Fyre <u>burners</u> <u>and valves</u> with this Real Fyre gas log set. Failure to do so may result in property damage or personal injury, and will void listings, certifications, and invalidate claims made to RHP. Contact your local Real Fyre dealer if you need more information.

This product is only warranted when used as part of a Robert H. Peterson Co. vented burner system.

During initial use, the logs will go through a curing process and will temporarily turn a darker color. This will last for approximately 6-8 hours (of burn time); then the logs will return to their original white color.


ROBERT H. PETERSON CO. • 14724 East Proctor Avenue • City of Industry, CA 91746

WARNING: This gas log set is for use with <u>R.H. Peterson Co.</u> burners (and parts) <u>ONLY.</u>

CAUTION: Burn hazard! Logs will remain hot for some time after use. If you need to reposition any log to maintain the proper layout, use heat resistant gloves or allow logs adequate time to cool before handling.


Failure to use Peterson burners and valves may result in a **DANGEROUS** situation and in property damage, personal injury or even death; will void listings and certifications; and will void any insurance coverage by R.H. Peterson Co. or our insurers.

CHARRED MOUNTAIN BIRCH LOG PLACEMENT INSTRUCTIONS (18/20" MODEL)




CHARRED MOUNTAIN BIRCH LOG PLACEMENT INSTRUCTIONS (24" & 30" MODELS)


This charred log set includes an ember screen and glowing embers. For G4 & G45 Series Burner Systems; refer to the main owner's manual for screen and embers installation. For G46 & "P" Series Burner Systems; DISCARD the screen and embers as they are not applicable.



CHARRED MOUNTAIN BIRCH LOG PLACEMENT INSTRUCTIONS (36" MODEL)


This charred log set includes ember screens and glowing embers. For G4 & G45 Series Burner Systems; refer to the main owner's manual for screen and embers installation. For G46 & "P" Series Burner Systems; DISCARD the screen and embers as they are not applicable.





CHARRED MOUNTAIN BIRCH LOG PLACEMENT INSTRUCTIONS (42" MODEL)

This charred log set includes ember screens and glowing embers. For G4 & G45 Series Burner Systems; refer to the main owner's manual for screen and embers installation. For G46 & "P" Series Burner Systems; DISCARD the screen and embers as they are not applicable.



Π

