



Requirements for Using a burning gas log set on Peterson's Real-Fyre 3 Unit Display (RFD-08)

If you are permitted by local authorities, codes and building management, you may turn on Real Fyre gas logs sets on this RFD-08 **only** for short periods, and **only** on an intermittent basis. This can be an attractive and cost-efficient way to show the beauty and convenience of our products.

NOTE: IF THE DISPLAY IS EQUIPPED WITH AN LED LIGHT ACCESSORY KIT (RFDL-08), BURNING IS NOT PERMITTED AS DAMAGE TO THE RFDL-08 WILL OCCUR.

You **must** follow these requirements if you are going to burn any products on this display:

1. Use **only** Peterson Real Fyre burners, controls, logs, glass, gems, nuggets, geo shapes etc.*
2. Be certain the log sets are set up and connected to the gas according to the instructions.
3. Assure all gas connections are tight and tested for leaks.
4. Be certain that there are **no combustibles** within 3 feet of the display.
5. Be sure the display is set in a safe, stable and supervised area. Remember, children may be in your store at any time. This display **must** be treated as an attended appliance per ANSI standards.
6. Do not place the display under a fire sprinkler head.
7. A working fire extinguisher must be in place close to any display where there is a burning unit.
8. You must train yourself and your employees to properly and safely use the burning gas log sets and how to use the fire extinguisher.
9. Each shelf must be marked "**Caution – Hot Surface**". Labels are included.
10. You **must** have an upstream gas on/off valve... and it **MUST** be turned to the off position when display is not in use.
11. You must use an RHP ignition system on any sets that burn. **No match lighting!!** This is an absolute requirement. No exceptions!
12. **Vented logs may be burned on the top shelf ONLY - NOT** on bottom shelves; vent-free logs may be burned on the bottom shelves.
13. Only **one log set may be lit** at a time.
14. Log sets may be burned for no more than **two (2) minutes** at a time.
15. A **five (5) minute** cooling period **must** be exercised before re-lighting the log set.
16. R.H. Peterson Co. will not be responsible for damage of any kind to persons or property, due to burning gas log sets, or any other use of this RFD-08 unit.

*The Flame Enhancer is NOT allowed to be burned on the RFD-08.